







With a footprint of only 735 x 855 mm and 7 trays, SNAKKY MAX allows a complete refreshment service offering a choice of snacks, confectionery, cans and bottles.

As you would expect from Necta, the Snakky Max is the operator's dream, as replenishing stocks couldn't be simpler, with pull out trays which tilt to allow easy access. To ensure client satisfaction, the Snakky Max has a sensor in the delivery area which detects if a product has actually been vended (option).

Designed to sit alongside the similarly sized Kikko Max in order to provide a full refreshment service, Snakky Max can also be banked with Astro, working in master/slave mode, and with Zenith.

TEMPERATURE

Uniform (5-8°C)

Varied (10-15°C in upper trays and 5-7°C in lower trays) with operating conditions of 32°C.

ELECTRONIC CONTROL

- 16-bit electronic control with incorporated Flash EPROM
- Automatic setup and reading of statistics with Flash application or Up-Key
- Remote monitoring via GSM technology (with the specific kit)

PAYMENT SYSTEMS

The payment systems and the electronic board are located inside a separate compartment, with independent access and slide-out opening for complete extraction, allowing work to take place in this area without affecting the temperature inside the product compartment. Snakky Max is pre-set for the installation of systems with Executive and MDB protocol, as well as validators.

The following can be installed on the same machine:

- Change-giver coin mechanism/validator
- Bill validator
- · Cashless system with key or card

ACCESSORIES

5 direct selection buttons (standard on some versions)
Vend detector system kit (standard on some versions)
Kit to block dispensing compartment (standard on some versions)
Coin box cover kit

Wall mounting bracket kit RS232 jack kit

GSM kit

EXAMPLE OF POSSIBLE CONFIGURATION

3 snack trays

15 selections / 219 products

1 bottle tray

6 selections / 36 products

3 can trays

18 selections / 108 products

1	13		13		3	140 mm
19	19	13	13	19	19	128 mm
13	13	13	13	13	13	130 mm
6	6	6	6	6	6	215 mm
6	6	6	6	6	6	112 mm
6	6	6	6	6	6	116 mm
6	6	6	6	6	6	116 mm

Snacks Bottles 0.5 litre PET Cans 0.33/0.25 litre

The numbers in the table indicate the product capacity



CHARACTERISTICS				
Height	1830 mm*			
Width	735 mm			
Depth	855 mm			
Depth with door open	1350 mm			
Weight	225 Kg			
Power supply voltage	230 V			
Power supply frequency	50 Hz			
Absorbed power	560 W			
Maximum operating conditions	32°C - 65% R. H.			
*+10 - 10 mm				

POWER CONSUMPTION For each hour of stand-by Ambient temperature Refrigerated box temperature 20°C 8efrigerated box temperature











N&W GLOBAL VENDING S.p.A.

Via Roma, 24 24030 Valbrembo (BG) Italy Ph. +39 035 606111 - Fax +39 035 606519